

DATASHEET



CU6RCD

13A RCD Protected Fused Spur Unit - 30mA (Type A)

www.mlaccessories.co.uk

MLA PART CODE	CU6RCD
DESCRIPTION	13A RCD Protected Fused Spur Unit - 30mA (Type A)
NET WEIGHT (KG)	0.155
FINISH	White
DIMENSIONS (MM)	Height - 86 Width - 86 Projection - 12
MINIMUM MOUNTING BOX DEPTH	35mm
CONSTRUCTION	Construction - Thermoset resin
IP RATING	IP20
INPUT VOLTAGE	230V 50Hz
EARTH TERMINAL	Yes
LOAD/MAX. LOAD	13A
TERMINAL TYPE	Captive
TERMINAL CAPACITY	2 x 2.5mm ² or 1 x 4.0mm ²
BUILT-IN TECHNOLOGY	Type A RCD
ADDITIONAL FEATURES	RCD trip current of 30mA. Double pole RCD contact break. Latching type RCD. Cable outlet at bottom with strain relief.
FUNCTION	RCD trip speed of less than 40ms
WARRANTY	2year(s)
MANUFACTURED IN ACCORDANCE WITH	BS 1363-4, BS 7288
ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN	5056270811537

Date Created: 31/08/2022 13:55

