

Technical Specification

CLICK® ScolmoreGROUP

Product Code: MD022SC-HT Description: 20A Ingot Double Pole Switch Module





Rear Housing: Nylon

Frequency (Hz) 50

Contacts: Silver "on-lay" Copper / Brass

Terminals: Brass

Terminal Torque Value (Nm) 1.2

General Information

Dimensions (mm) 41 (W) x 52.5 (H) x 22 (D)

Finish Satin Chrome

Materials Rocker Switch: Urea

Switch Cover: Stainless Steel
Terminal Screws: Steel & Yellow Passivated

Internal Busbars: Formed Pressed Brass

Rated Voltage (V~) (Ue) 250

Resistive Load Rating (A) 20

Termination Type Screw

Terminal Size (mm) Ø4.4

Terminal Capacity - Solid (mm²) 3 x 2.5 or 2 x 4

Modular Rocker Switches Yes

Double Pole Switch Yes

Product Marking Hot Tap

Minimum Back Box Depth (mm) 25 (35 Flat Plate)

Operational Temperature (°C) -5 to +40

Warranty (Years) 10

Additional Information F

For cleaning / polishing of products, use only a soft, dry, clean cloth.

Ensure that the mains supply is isolated before commencing installation and refer to the circuit

diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

