Straight Plug IP44

- Designed for ease of assembly and wiring.
- Twist grip cable gland locking system.
- Rated current up to 32A.
- IK08 rating as per IEC/EN 62262.
- Thermoplastic grip material.

PM16/1000FPB

Straight plug

TECHNICAL DATA	
Rated current	16A
Frequency	50/60Hz
Poles	2P+⏚
Protection degree	IP44
Nominal Operating Voltage2	N/A
Clock Position	4h
Rated operating voltage	110V
Manufacturing material	Thermoplastic

REGISTRY	
Net weight	0.11KG
EAN Code	8014950031405
Gross Weight	0.12KG
Min order quantity	1

REFERENCE STANDARDS	STANDARDS
EN 60309-1:1999/A1:2007	2014/35/EU (LVD)
EN 60309-2:1999	2012/19/EU (WEEE)
EN 50581:2012	2011/65/EU (RoHS)
EN 60309-1:1999	
EN 60309-1:1999/A2:2012	
EN 60309-2:1999/A1:2007	
EN 63000:2018	
EN 60309-2:1999/A2:2012	
EN 60309-1:1999/A1AC:2014	

Lewden
Unit 4, Bradbury Drive, Springwood Industrial Estate - Braintree - Essex - CM7 2SD - UK - Phone: +44 01376 336200 - www.lewden.co.uk - sales@lewden.co.uk