

# Technical Specification

**Product Code:** VPBN156BK

**Description:** Non-Isolated Single Satellite Outlet



### General Information

<b>Plate Dimensions (mm)</b>	88 (W) x 88 (H) x 8 (D)
<b>Dimensions With Gasket (mm)</b>	91 (W) x 91 (H) x 9 (D)
<b>Plate Fixing Centres - Horizontal (mm)</b>	60.3
<b>Style</b>	Victorian
<b>Finish</b>	Black Nickel
<b>Insert Colour</b>	Black
<b>Gasket Colour</b>	Black
<b>Materials</b>	Front Plate: Stainless Steel Terminals: Brass Gasket: Nylon
<b>Anti Microbial Certified</b>	No
<b>Termination Type</b>	Screw
<b>Isolated</b>	No
<b>Non-Isolated</b>	Yes
<b>Non-Isolated Comments</b>	Enables 2 way signal transmission
<b>Shielded</b>	No
<b>Minimum Back Box Depth (mm)</b>	16
<b>Ingress Protection</b>	IP20
<b>Operational Temperature (°C)</b>	-5 to +40
<b>Warranty (Years)</b>	10

Insert: Urea  
Earth Plate: Mild Steel

### Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.  
Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.  
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.  
Isolated socket will filter out any interference, if a 2 way signal is required, i.e. for use with satellite hard wire extensions, then a non-isolated outlet is required.