

Technical Specification



Page 1 of 1 (20/02 Errors & Omissions exclu

Product Code: VPSC504GY

Description: 50A Ingot 2 Gang Double Pole Switch With 13A Double Pole Switched Socket Outlet

 $(\cap$



General Information

Plate Dimensions (mm) Dimensions With Gasket (mm) Plate Fixing Centres - Horizontal (mm) Style Finish Insert Colour Gasket Colour Materials		Insert & Rear Housing: Urea Terminal Screws: Steel & Yellow Passivated Internal Busbars: Formed Pressed Brass Gasket: Nylon
Anti Microbial Certified	No	
Rated Voltage (V~) (Ue)	250	Frequency (Hz) 50
Resistive Load Rating (A)	45	
Termination Type	Screw	
Terminal Size (mm)	Ø6 Termina	I Torque Value (Nm) 2.5
Terminal Capacity - Solid (mm ²)	1 x 16	
Double Pole Switch	Yes	
Twin Earth Terminals	Yes	
Product Marking	On, Off, Socket, Cooker	
Minimum Back Box Depth (mm)	35	
Ingress Protection	IP20	
Operational Temperature (°C)	-5 to +40	
Warranty (Years)	10	
Ensure th diagram	or cleaning / polishing of products, use only a soft, dry, clean cloth. nsure that the mains supply is isolated before commencing installation and refer to the circuit iagram with the relevant product. are earth cables must always be covered with appropriate sleeving and wired to the earth terminal.	

Scolmore House, Mariner, Lichfield Road Industrial Estate, Tarnworth, Staffordshire, B79 7UL United Kingdom T: +44 (0)1827 63454 | F: +44 (0)1827 63362 E: sales@scolmore.com | W: scolmore.com